



- TRONICS, INC.

SETTING THE STANDARD FOR SERVICE

1212 NE 5TH ST. REDMOND, OR 97756

PHONE 541-548-2110 FAX 541-548-2117

www.aquatronics.com aquatron@aquatronics.com

Digi-7 Cable Locator

Specifications:

Receiver:

Operating Frequency	117.85KHz
Antenna mode	Switchable between Null or Peak display mode
Audio Indication	Variable pitch response on each side of target conductor
Visual Indication	Large LCD display contains: Left/Right guidance display arrows with centering ability, Analog LCD Bargraph, and Absolute Digital Signal Strength readout. (0-999)
Operation Modes	Fully automatic with left/right guidance (volume control is only adjustment.) Fully manual (user set's gain control; operates like A-7 Cable Commander)
Depth Measurement	Bubble level triangulation
Operating Temp	-10°F to 125°F
Battery Type/Life	Six 1.5V. AA-size / 50 hours
Weight	4 lbs. 1oz.

*Equipped with external antenna jack for cable phasing and identification.

Transmitter:

Operating Frequency	117.85KHz
Indicator	Low battery warning, Impedance matching tap setting numerical Readout
Impedance Matching	Automatic with manual override for mismatching purposes
Output modes	Direct output jack and internal Inductive Antenna
Operating Temp	-25°F to 125°F.
Battery Type	Six 1.5V. D-size
Battery life	50 Hours
Weight	Approx. 6 lbs.